

# Lifting up Your VW: Right Side

---

- **READ THE BENTLEY or HAYNES MANUAL FIRST!**
- You will need a FLAT surface to complete this repair for your safety.
- **READ ALL OF THIS PROCEDURE SEVERAL TIMES SO THAT YOU UNDERSTAND IT. DO NOT PERFORM THE PROCEDURE OUT OF ORDER. THIS WILL RESULT IN DEATH OR SERIOUS INJURY.**
- Read our [Safety](#) page too.

We have available for download the complete procedure on our [DOWNLOADS](#) page

## TOOLS NEEDED:

1. Floor Jack (4000 lbs. capacity)
2. 2 jack stands
3. 2 Wheel Chocks
4. Tire iron or "Tire Star"



## Procedure for Lifting the right side

1. Remove hub caps on Right side with a screwdriver or tire iron



2. Break loose all lug bolts on tire(s)



3. Chock left side tires.



4. Place floor jack under the jack hole.



5. Jack up the vehicle to a height of a comfortable level for you to crawl underneath  
6. **BEFORE GETTING UNDER THE VW:** On the rear place the Jack stands under the torsion arm bushing retainer as shown in the picture:



7. Remove all lug bolts and place them in the hub cap.



8. Remove the tire from the Brake Drum.



Copyright 2005!

BURG II